



泰行天下 昊跃四海

- ◆ Skid Steer Tyre
- ◆ Industrial Tractor Tyre
- ◆ Forklift Tyre
- ◆ Solid Tyre
- ◆ Agricultural Tyre
- ◆ Implement Tyre
- ◆ OTR Tyre
- ◆ Sand Tyre
- ◆ Trailer Tyre
- ◆ Truck Tyre
- ◆ ATV Tyre

PROFESSIONAL TYRE MANUFACTURER

泰昊轮胎  
TAIHAO TYRE

ADD: QIANLOU RUBBER INDUSTRIAL ZONE, MINGCUN  
TOWN PINGDU CITY, QINGDAO, CHINA  
TEL: 86-0532-85611626  
FAX: 86-0532-85610387  
Website: [www.taihaotyre.com](http://www.taihaotyre.com)  
Email: [sales@taihaotyre.com](mailto:sales@taihaotyre.com)

青岛泰昊轮胎有限公司  
QINGDAO TAIHAO TYRE CO.,LTD

2024  
NEW VERSION

# COMPANY INTRODUCTION

Qingdao Taihao Tyre Co. Ltd is a professional manufacturer of tyres, was established in 2007, located in Pingdu city, Qingdao, Shandong province. Employ over 400 staff, The main products are OTR Tyre, Agricultural Tyre, Skid Steer Tyre, Industrial Tyre, Forklift Tyre, Trailer Tyre, Sand Tyre, Implement Tyre, Bias Light Truck Tyre and ATV Tyre ect. Credited with ISO9001, CCC, DOT, SGS, SMITHERS, REACH certifications, have become one of the leading tyre factory in domestic market. The company's brands "TAIHAO" "ALWAYS RUN" "PLUSWAY" are distributed to more than 150 countries and all received with positive feedback by global partners.

We have been focusing on tyre's design, research and development, quality control, brand building and management. Our technical team is always ready to discuss with you about new productive opportunities and to design the most suitable tyres with the cutting-edge technology to expand your market profitability and win the market share.

We always stick to the excellent quality, reasonable price, prompt delivery and excellent service. We sincerely hope to build good and long term cooperation with all customers. We trust that we are to be your best supplier and partner.



Mixing



Extruding



Calendering



Building



Building



Green Tyre



Vulcanization-1



Vulcanization-2



Vulcanization-3



Tyre Testing



Finished products



Product Wrapping



# Skid Steer Tyre(Tubeless)

# INDUSTRIAL TYRE



Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
10-16.5	10	773	264	8.3	2135	520	SKS-1
12-16.5	12	831	307	9.8	2865	550	SKS-1
14-17.5	14	921	349	10.5	3875	550	SKS-1
11L-16	12	808	279	8LB	1250	440	SKS-1



**SKS-1**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
10-16.5	12	795	264	8.25	2375	620	SKS-4
12-16.5	14	852	307	9.75	3075	620	SKS-4



**SKS-4**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
10-16.5	12	795	264	8.25	2375	620	SKS-2
12-16.5	14	852	307	9.75	3075	620	SKS-2



**SKS-2**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
10-16.5	12	815	264	8.25	2375	620	SKS-5
12-16.5	14	869	307	9.75	3075	620	SKS-5
12.5/80-18	12	1027	308	9	2625	370	SKS-5
16.9-28	12	1410	429	W15L	3450	260	SKS-5



**SKS-5**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
10-16.5	12	815	264	8.25	2375	620	SKS-3
12-16.5	14	869	307	9.75	3075	620	SKS-3
11L-16	12	855	279	8LB	1250	440	SKS-3
12.5/80-18	12	1027	308	9	2625	370	SKS-3
14-17.5	14	962	349	10.5	3875	550	SKS-3



**SKS-3**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
10-16.5	12	795	264	8.25	2375	620	SKS-6
12-16.5	14	852	307	9.75	3075	620	SKS-6



**SKS-6**

# Industrial Tractor Tyre (Tubeless)

# INDUSTRIAL TYRE



Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
10.5/80-18	10	925	274	9	1935	350	R-4(A)
12.5/80-18	12	985	308	9	2625	370	R-4(A)



**R-4(A)**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
15.5/80-24 (400/80-24)	12	1240	395	W13	4000	150	R-4(D)



**R-4(D)**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
16.9-24	12	1309	429	W15L	3250	260	R-4(B)
16.9-28	12	1410	429	W15L	3450	260	R-4(B)
19.5L-24	12	1314	495	DW17	3450	230	R-4(B)
18.4-26	12	1436	467	DW16	2985	230	R-4(B)



**R-4(B)**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
405/70-20 (16/70-20)	14	1075	410	13.0	3750	350	R-1M
405/70-24 (16/70-24)	14	1175	410	13.0	3950	350	R-1M



**R-1M**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
12.5/80-18	12	1001	350	9	2625	370	R-4(C)
16.9-28	12	1435	430	W15L	3450	260	R-4(C)
18.4-26	12	1450	467	DW16	2985	230	R-4(C)



**R-4(C)**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
11L-15	10	813	279	8LB	1060	360	F-3
11L-16	12	838	279	8LB	1250	420	F-3



**F-3**

# Industrial Tractor Tyre (Tubeless)

# INDUSTRIAL TYRE



Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
16.9-24	12	1236	429	15	3250	260	TH801
16.9-28	12	1435	430	15	3450	260	TH801
19.5L-24	12	1314	495	17	3455	230	TH801



**TH801**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
16.9-24	12	1236	429	15	3250	260	TH804
16.9-28	12	1435	430	15	3450	260	TH804



**TH804**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
19.5L-24	12	1314	495	17	3455	230	TH802



**TH802**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
23.1-26	14	1500	595	DW20	5600	280	R-3



**R-3**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
12.5/80-18	12	1001	350	9	2625	370	TH803
16.9-28	12	1435	430	15	3450	260	TH803



**TH803**

## Military Tyre

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
1300x530-533 (530/70-21)	16	1300	530	440x533	4775	525	E-2



**E-2**

# FORKLIFT TYRE



Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
5.00-8	10	470	137	3.50D	1150	1000	TH202
6.00-9	10	540	160	4.00E	1505	860	TH202
6.50-10	10	590	175	5.00F	1655	790	TH202
7.00-12	14	676	190	5.00S	2590	1000	TH202
7.00-15	14	750	200	5.5	3140	1000	TH203
7.50-15	14	780	215	6	3375	925	TH202
8.25-15	14	840	235	6.5	3775	830	TH202
18*7-8	14	465	173	4.33R	1505	970	TH202
21*8-9	14	535	200	6.00E	2040	1000	TH202
23*10-12	14	597	254	8.00G	2950	830	TH202
23*9-10	16	595	225	6.50F	2810	1030	TH202
250-15	16	735	250	7.5	3865	930	TH202
27*10-12	14	690	255	8.00G	3285	860	TH202
28*9-15 (8.25-15)	14	706	220	7	3050	970	TH202
300-15	20	840	300	8	5940	930	TH203
10.00-20	16	1055	278	7.5	6030	790	TH202
12.00-20	20	1125	315	8.5	7400	1000	TH202



**TH202**



**TH203**



**TH200**

## Solid Tyre

Size	Rim	Overall Diameter (mm)	Section Width (mm)	Load capacity(kg) Balance forklift						Other Forklifts (kg) 16km/h	Pattern
				10km/h		16km/h		26km/h			
				Drive	Steer	Drive	Steer	Drive	Steer		
4.00-8	3	423	121	1090/840	995/765	925/710	710	TH200			
5.00-8	3	469	146	1255/965	1145/880	1060/815	815	TH200			
200/50-10	6.5	460	221	2910/2240	2665/2050	2470/1900	1900	TH200			
6.00-9	4	545	160	1975/1520	1805/1390	1675/1290	1290	TH200			
6.50-10	5	597	178	2715/2090	2485/1910	2310/1775	1775	TH200			
7.00-9	5	578	186	2670/2055	2440/1875	2260/1740	1740	TH200			
7.00-12	5	683	192	3105/2390	2835/2180	2635/2025	2025	TH200			
7.00-15	5.5	759	204	3700/2845	3375/2595	3150/2410	2410	TH200			
7.50-15	5.5	774	215	3805/2925	3470/2670	3225/2480	2480	TH200			
7.50-16	5.5	820	220	4035/3105	3685/2835	3425/2635	2635	TH200			
28*9-15 (8.15-15)	7	706	225	4060/3125	3710/2855	3445/2650	2650	TH200			
8.25-12	5	735	236	3425/2635	3125/2405	2905/2235	2235	TH200			
8.25-15	5.5	847	236	4305/3310	3925/3020	3640/2800	2800	TH200			
8.25-20	6.5	992	236	5165/4305	4715/3930	4380/3650	3650	TH200			
9.00-16	6.5	884	259	5290/4070	4830/3715	4485/3450	3450	TH200			
9.00-20	7	1038	259	6365/5305	5815/4845	5400/4500	4500	TH200			
10.00-20	7.5	1073	278	7075/5895	6460/5385	6000/5000	5000	TH200			
11.00-20	7.5	1095	300	7470/6225	6820/5685	6330/5275	5275	TH200			
12.00-20	8	1180	310	8640/7200	7885/6570	7320/6100	6100	TH200			
21*8-9	6	535	207	2890/2225	2645/2035	2455/1890	1890	TH200			
15*4 1/2-8	3	380	114	1005/775	915/705	805/655	655	TH200			
16*6-8	4.33	418	162	1545/1190	1410/1085	1305/1005	1005	TH200			
18*7-8	4.33	457	170	2430/1870	2215/1705	2060/1585	1585	TH200			
23*9-10	6.5	595	225	3730/2870	3405/2620	3160/2430	2430	TH200			
23*10-12	8	595	261	4450/3425	4060/3125	3770/2900	2900	TH200			
27*10-12	8	683	261	4595/3535	4200/3230	3900/3000	3000	TH200			
250-15	7.5	735	250	5595/4305	5510/3930	4745/3650	3650	TH200			
300-15	8	838	300	6895/5305	6300/4845	5850/4500	4500	TH200			

# Tractor Tyre

# AGRICULTURAL TYRE



MR-1

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
12.4-36	12	1464	315	W11	1925	330	MR-1
12.4-38	12	1514	315	W11	1905	310	MR-1
14.9-24	10	1265	378	W13	1990	230	MR-1
14.9-38	14	1621	378	W13	2725	320	MR-1
15.5-38	10	1570	395	W14	2320	230	MR-1
18.4-30	12	1550	467	W16L	3180	230	MR-1
18.4-34	12	1655	467	W16L	3375	230	MR-1
20.8-42	12	1935	528	W18L	3750	190	MR-1
23.1-30	14	1705	587	DW20	4200	200	MR-1
24.5-32	16	1803	622	DW21	4500	210	MR-1
30.5L-32	16	1819	775	DW27	5000	180	MR-1

# Tractor Tyre

## AGRICULTURAL TYRE



Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
5.00-12	8	590	145	4.00E	345	280	R-1
5.50-17	6	750	138	4.00E	400	280	R-1
6.00-12	8	640	165	4.50E	450	330	R-1
6.00-14	8	690	165	4.50E	530	330	R-1
6.00-16	8	745	165	4.50E	550	360	R-1
6.50-16	8	765	180	5.00F	660	330	R-1
7.50-16	8	810	205	5.50F	770	280	R-1
7.50-20	8	910	205	5.50F	915	280	R-1
8.3-20	8	895	210	W7	850	310	R-1
8.3-24	8	995	210	W7	830	250	R-1
8.5-20	8	875	195	W7	780	250	R-1
9.5-16	6	860	240	W8	800	210	R-1
9.5-20	8	950	240	W8	955	280	R-1
9.5-24	8	1050	240	W8	1110	280	R-1
9.5-28	8	1140	240	W8	1185	280	R-1
9.5-32	8	1250	240	W8	1260	280	R-1
11.2-20	8	1005	285	W10	1085	240	R-1
11.2-24	10	1105	285	W10	1380	300	R-1
11.2-28	8	1205	285	W10	1305	240	R-1
11-32	6	1360	305	W10	1000	140	R-1
12.4-24	10	1160	315	W11	1640	290	R-1
12.4-28	8	1260	315	W11	1510	230	R-1
13.6/12-38	10	1565	345	W11	2215	250	R-1
13.6-20	8	1060	345	W12	1400	160	R-1
13.6-24	10	1210	345	W12	1790	250	R-1
13.6-28	10	1310	345	W12	1910	250	R-1
14.9-24	10	1265	378	W13	1990	230	R-1
14.9-26	10	1315	378	W13	2055	230	R-1
14.9-28	10	1365	378	W13	2120	230	R-1
14.9-30	10	1415	378	W13	2190	230	R-1
15-24	10	1330	410	DW14	2800	280	R-1
15.5-38	10	1570	395	W14	2320	230	R-1
16.9-24	10	1335	430	W15L	2230	200	R-1
16.9-28	10	1435	430	W15L	2380	200	R-1
16.9-30	12	1485	430	W15L	2730	240	R-1
16.9-34	10	1585	430	W15L	2605	200	R-1
16.9-38	10	1685	429	W15L	2760	200	R-1
18.4-26	12	1450	467	DW16	2985	230	R-1
18.4-30	12	1550	467	W16L	3180	230	R-1
18.4-34	12	1655	467	W16L	3375	230	R-1
18.4-38	12	1755	467	W16L	3575	230	R-1
20.8-38	12	1835	528	W18L	4000	200	R-1
23.1-26	12	1605	587	DW20	3610	170	R-1



R-1



R-1

### Irrigation Tyre

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
13.6-24	10	1210	345	W12	1790	250	R-1
14.9-24	10	1265	378	W13	1990	230	R-1
11.2-38	10	1465	285	W10	1555	300	R-1



R-1

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
14.9-24	10	1265	378	W13	1990	230	TH600



TH600





# Tractor Tyre

## AGRICULTURAL TYRE



R-2

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
14.9-24	8	1305	378	W13	1600	180	R-2
14.9-28	8	1406	378	W13	1700	180	R-2
23.1-30	16	1829	610	DW20	4000	225	R-2
24.5-32	16	1862	622	DW21	3560	140	R-2

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
19.5L-24	12	1383	495	W17	2145	210	R-2
23.1-26	12	1662	587	DW20	3610	170	R-2
28L-26	14	1672	715	DW25	4745	170	R-2
18L-24	6	1304	445	W15L	1340	230	R-2
20L-24	6	1382	495	DW16	1340	230	R-2



R-2

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
6.00-12	6	690	160	4.50E	425	270	PR-1
6.00-14	6	710	165	4.50E	450	250	PR-1
6.50-16	6	830	165	5.00F	565	250	PR-1
7.50-16	6	890	195	5.50F	750	300	PR-1
8.3-20	8	950	210	W7	1130	350	PR-1
8.3-24	8	1050	210	W7	1275	330	PR-1
9.5-24	8	1150	240	W8	1475	290	PR-1
11.2-24	10	1205	285	W10	1800	310	PR-1
11-32	10	1460	305	W10	1400	250	PR-1
12.4-24	8	1245	315	W11	1980	230	PR-1
12.4-28	6	1315	315	W11	1785	200	PR-1
13.6-24	10	1246	345	W12	1790	250	PR-1
13.6-38	10	1710	345	W12	2780	250	PR-1
14.9-24	10	1410	378	W13	1990	230	PR-1
14.9-26	10	1460	378	W13	2040	230	PR-1
14.9-28	10	1510	378	W13	2150	230	PR-1
14.9-30	10	1560	378	W13	2190	230	PR-1
16.9-28	12	1533	430	W15L	2540	230	PR-1
16.9-30	10	1585	430	W15L	2455	200	PR-1
16.9-34	10	1685	430	W15L	3385	220	PR-1
18.4-30	12	1597	467	W16L	3180	230	PR-1
18.4-38	12	1855	467	W16L	3575	180	PR-1
20.8-38	12	1972	528	W18L	4100	200	PR-1



PR-1

# Tractor Tyre

## AGRICULTURAL TYRE



Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
10.00-16	10	910	275	W8L	1325	340	F-2(4RIB)
11.00-16	10	970	315	W10L	1485	310	F-2(4RIB)



F-2(4RIB)

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
5.50-16	8	685	150	4.00E	625	420	TH657
6.00-16	8	740	160	4.00E	675	450	TH657



TH657

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
4.00-12	4	535	110	3.00D	250	340	F-2(3RIB)
4.00-14	6	590	110	3.0DD	315	450	F-2(3RIB)
5.00-15	6	665	140	4J	465	420	F-2(3RIB)
5.50-16	6	710	150	4.00E	525	370	F-2(3RIB)
6.00-16	8	740	160	4.00E	675	450	F-2(3RIB)
6.50-16	8	760	175	4.50E	735	420	F-2(3RIB)
7.50-16	8	810	205	5.50F	870	370	F-2(3RIB)
7.50-18	8	860	205	5.50F	945	370	F-2(3RIB)
9.00-16	8	860	235	6LB	1080	310	F-2(3RIB)
10.00-16	10	910	275	W8L	1325	340	F-2(3RIB)
11.00-16	10	970	315	W10L	1485	310	F-2(3RIB)



F-2(3RIB)

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
9.00-16	12	894	276	6LB	1245	390	F2-3



F2-3

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
10.00-16	10	910	275	W8L	1325	340	TF-2



TF-2

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
11L-15	8	775	280	W8L	1130	220	I-1
11L-16	12	803	279	W8L	1510	360	I-1
7.50-16	10	785	203	5.50F	1240	400	I-1
10.5/80-18	10	885	274	9	1935	370	I-1



I-1

# Tractor Tyre

## AGRICULTURAL TYRE



Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
7.00-12	12	683	192	5.00F	1050	390	IMP100
10.0/80-12	8	715	264	9	1240	310	IMP100
10.0/75-15.3	10	765	264	9	1525	390	IMP100
11.5/80-15.3	12	854	290	9	2145	410	IMP100
12.5/80-15.3	14	869	297	9	1650	430	IMP100



IMP100

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
16.5/70-18	14	1065	425	W13	3650	410	TH101



TH101

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
400/60-15.5	16	874	404	13	2240	400	I-3
500/45-22.5	16	1022	503	16	2360	280	I-3
500/50-17	14	950	500	16	480	4125	I-3



I-3

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
6.50-16	10	760	182	4.50E	975	530	TH672
7.00-16	12	790	202	5.5	1090	530	TH672



TH672

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
400/60-15.5	16	874	404	13	2240	400	RIB100



RIB100

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
26*7.5-12	4	680	205	5.50F	370	180	TH900



TH900

# OTR Tyre

# OFF-THE-ROAD TYRE



- Non-direction pattern design provide good traction and skid resistance
- Excellent wear and cut resistance performance.
- Suitable to heavy dump trucks, scrapers and loaders operation under many conditions.



Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max Load(Kg)		Inflated Pressure(kpa)		Pattern
					10km/h	50km/h	10km/h	50km/h	
750-16	10	805	215	6.00/G	860	/	530	/	E3/L3(w1)
900-16	14	890	255	6.50H	1120	/	260	/	E3/L3(w1)
12.00-16	16	840	240	6.50H	1705	/	680	/	E3/L3(w1)
16/70-20	16	1075	410	13	5600	3350	450	350	E3/L3(w1)
16/70-24	16	1175	410	13	5600	3350	450	350	E3/L3(w1)
20.5/70-16	16	1075	410	8.50H	/	2850	/	350	E3/L3(w1)
15.5-25	16	1275	395	12.00/1.3	6750	3850	525	325	E3/L3(w1/w2)
17.5-25	16	1350	445	14.00/1.5	7300	4250	475	300	E3/L3(w1/w2)
17.5-25	20	1350	445	14.00/1.5	8250	5000	575	400	E3/L3(w1/w2)
20.5-25	20	1490	520	17.00/2.0	9500	6000	450	325	E3/L3(w1/w2)
20.5-25	24	1490	520	17.00/2.0	10300	6700	525	400	E3/L3(w1/w2)
23.5-25	20	1615	595	19.50/2.5	10900	7300	375	300	E3/L3(w1/w2)
23.5-25	24	1615	595	19.50/2.5	12500	8000	475	350	E3/L3(w1/w2)
26.5-25	24	1750	675	22.00/3.0	14000	9250	400	300	E3/L3(w1/w2)
26.5-25	28	1750	675	22.00/3.0	15500	10000	475	350	E3/L3(w1/w2)
26.5-25	32	1750	675	22.00/3.0	17000	11200	550	425	E3/L3(w1/w2)
29.5-25	28	1875	750	25.00/3.5	17500	11500	425	325	E3/L3(w2)
29.5-25	32	1875	750	25.00/3.5	20000	12950	525	400	E3/L3(w2)
14.00-24	20	1370	375	10	8500	4625	700	475	E3/L3(w1)
14.00-24	24	1370	375	10	9500	5150	850	575	E3/L3(w1)
14.00-24	28	1370	375	10	10000	5600	925	650	E3/L3(w1)
14.00-25	24	1370	375	10.00/1.5	9500	5150	850	575	E3/L3(w1)
14.00-25	28	1370	375	10.00/1.5	10000	5600	925	650	E3/L3(w1)
14.00-25	32	1370	375	10.00/1.5	10900	6150	1050	750	E3/L3(w1)
16.00-25	28	1495	430	11.25/2.0	11500	6700	750	575	E3/L3(w1)
18.00-25	28	1615	500	13.00/2.5	13600	8000	650	500	E3/L3(w1/w2)
18.00-25	32	1615	500	13.00/2.5	15000	8750	750	575	E3/L3(w1/w2)
18.00-25	36	1615	500	13.00/2.5	16000	9250	850	625	E3/L3(w1/w2)
18.00-25	40	1615	500	13.00/2.5	17000	9700	950	700	E3/L3(w1/w2)



**E3/L3(W1)**



**E3/L3(W2)**

# OFF-THE-ROAD TYRE



Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max Load (Kg)		Inflated Pressure (kpa)		Pattern
					50km/h	50km/h	50km/h	50km/h	
825-16	12	855	235	6.50H	650	210			E3/L3(W3)
1200-16	16	840	240	6.50H	1705	680			E3/L3(W3)



**E3/L3(W3)**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
17.5-25	16	1400	445	14.00/1.5	7300	475	L4



**L4**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
17.5-25	20	1400	445	14.00/1.5	8250	575	L5
20.5-25	24	1550	520	17.00/2.0	10300	525	L5
23.5-25	24	1675	595	19.50/2.5	12500	475	L5
26.5-25	28	1800	675	22.00/3.00	15500	475	L5



**L5**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max Load (kg)		Inflated Pressure (kpa)		Pattern
					10km/h	50km/h	10km/h	50km/h	
23.5-25	20	1615	595	19.50/25	10900	7300	375	300	E3/L3(W4)
23.5-25	24	1615	595	19.50/25	12500	8000	475	50	E3/L3(W4)



**E3/L3(W4)**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
20.5/70-16	16	950	400	8.5H	2850	350	G2
16/70-20	14	1070	410	13	5150	450	G2



**G2**

# OTR Tyre

# OFF-THE-ROAD TYRE



## Grader Loader Tyre

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max Load(Kg)		Inflated Pressure(kpa)		Pattern
					10km/h	50km/h	10km/h	50km/h	
1300-24	12	1278	333	8.00TG	5600	2725	450	300	G2/L2
1400-24	16	1348	362	8.00TG	7300	3650	550	350	G2/L2



**G2/L2**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max Load(Kg)		Inflated Pressure(kpa)		Pattern
					10km/h	50km/h	10km/h	50km/h	
1300-24	12	1278	333	8.00TG	5600	2725	450	300	G2/L2
1400-24	16	1348	362	8.00TG	7300	3650	550	350	G2/L2
15.5-25	12	1275	395	12.00/1.3	5600	3250	400	250	G2/L2
17.5-25	16	1350	445	14.00/1.5	7300	4250	475	300	G2/L2
20.5-25	16	1493	521	17.00/2.0	8250	4000	350	225	G2/L2
23.5-25	16	1617	597	19.50/2.5	9500	4750	300	200	G2/L2



**G2/L2**

## Excavator Tyre

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
9.00-20	14	1038	259	7.0	5195	760	G2/L2
10.00-20	16	1073	278	7.5	6085	790	G2/L2



**Excavator G2/L2**

## Sand Tyre



**TH800**

**TH808**

**TH818**

**TH828**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
14.00-20	18	1215	332	10.00	4125	245	TH800/TH808 TH818/TH828

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
16.00-20TT	18	1330	388	10.00	4350	325	TH828



**TH828**

# Small Trailer Tyre

# TRAILER TYRE



**TH300**

**TH301**

**TH302**

**TH777**

Metric Tire Size	Wheel Diameter (inches)	Load in KG	Load Range Load Index	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Max PSI LBS rated	Pattern
175/80D	13	615	C	6	610	177	50	TH301
205/75D	14	800	C	6	664	203	50	TH301
205/75D	15	825	C	6	689	203	50	TH300/TH301
225/75D	15	1,150	D	8	719	223	65	TH301
235/80D	16	1,360	E	10	782	236	80	TH301

Metric Tire Size	Wheel Diameter (inches)	Load in KG	Load Range Load Index	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Max PSI LBS rated	Pattern
700-15	15	1,395	E	10	750	200	75	TH302
750-16	16	1,650	F	12	850	215	90	TH302
750-17	17	1,439	F	10	843	212	90	TH777

Size	PR	Rim	Max Load(IBS)		Inflated Pressure (PSI)		Load Range	Pattern
			Single	Dual	Single	Dual		
1000-20	14	7.50	6175	5750	100	90	G	TH303



**TH303**

Size	PR	Rim	Max Load(IBS)		Inflated Pressure (PSI)		Load Range	Pattern
			Single	Dual	Single	Dual		
11-22.5	14	8.25	6175	5750	100	90	G	TH303



**TH303**

## Mobile Home Tyre

Metric Tire Size	Wheel Diameter (inches)	Load in KG	Load Range Load Index	Ply Rating	Overall Diameter	Section Width	Max PSI LBS rated	Pattern
8-14.5	16	1,380	E	14	706	203	90	TH304



**TH304**

# TRUCK TYRE



Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
6.00-13	8	655	170	4.50B	650	420	TH501
6.00-14	8	680	170	41/2J	690	420	TH501
6.00-15	8	705	170	4.50E	730	420	TH501
6.50-16	8	750	185	5.50F	850	420	TH501



**TH501**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
4.00-12	4	535	110	3.00D	250	340	LUG
4.00-14	4	590	110	3.00D	270	340	LUG
4.00-16	4	640	110	3.00D	300	340	LUG
4.50-14	8	606	122	3.00D	580	520	LUG
4.50-16	6	655	122	3.00D	462	450	LUG
5.00-14	8	628	130	4J	500	420	LUG
5.00-16	6	685	140	4.00E	480	390	LUG
5.50-16	6	710	150	4.00E	525	370	LUG
6.00-16	10	730	170	4.50E	850	530	LUG
7.00-16	10	775	200	5.50F	1090	530	LUG
7.50-16	14	805	215	6.00G	1500	730	LUG
7.50-20	14	935	215	6.0	1900	810	LUG
8.25-16	14	855	235	6.50H	1700	630	LUG
8.25-20	14	974	236	6.5H	2240	810	LUG
9.00-20	16	1018	259	7.0	2900	880	LUG



**LUG**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
4.50-12	12	545	127	3.00B	535	550	TH500



**TH500**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
6.50-15	8	730	180	4.50E	825	420	TH502
6.50-16	8	750	185	5.50F	850	420	TH502
7.00-16	10	775	200	5.50F	1090	530	TH502
7.50-16	14	805	215	6.00G	1500	730	TH502



**TH502**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
6.00-13	8	655	170	4.50B	650	420	RIB
6.00-14	8	680	170	41/2J	690	420	RIB
6.00-15	8	705	170	4.50E	730	420	RIB
6.50-14	8	705	180	41/2J	775	420	RIB
6.50-16	8	750	185	5.50F	850	420	RIB
7.00-15	10	750	200	5.50F	1030	530	RIB
7.00-16	10	775	200	5.50F	1090	530	RIB
7.50-15	10	780	215	6.00G	1215	530	RIB
7.50-16	14	805	215	6.00G	1500	730	RIB
8.25-16	14	855	235	6.50H	1700	630	RIB
9.00-20	16	1018	259	7.0	2900	880	RIB



**RIB**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
7.50-16	14	805	215	6.00G	1500	730	TH503
8.25-16	16	855	235	6.50H	1800	730	TH503



**TH503**



# TRUCK TYRE



Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
7.50-16	14	805	215	6.00G	1500	730	TH506
7.00-16	14	775	200	5.50F	1320	730	TH506
7.00-15	12	750	200	5.50F	1150	630	TH506



**TH506**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
7.50-16	14	816	215	6.00G	1500	730	TH669A
8.25-16	16	867	235	6.50H	1800	730	TH669A



**TH669A**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
6.50-16	12	761	185	5.50F	1060	630	TH505
7.00-16	14	785	200	5.50F	1320	730	TH505
7.50-16	14	816	215	6.00G	1500	730	TH505
8.25-16	16	867	235	6.50H	1800	730	TH505



**TH505**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
6.00-13	12	655	170	4.50B	825	630	TH702
6.00-14	10	691	170	41/2J	800	530	TH702



**TH702**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
6.50-16	12	761	185	5.50F	1060	630	TH504
7.00-16	14	785	200	5.50F	1320	730	TH504
7.50-16	14	816	215	6.00G	1500	730	TH504
8.25-16	16	867	235	6.50H	1800	730	TH504



**TH504**

Size	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Load capacity (kg)	Inflated Pressure (kpa)	Pattern
7.50-16	16	816	215	6.00G	1650	830	TH702C
9.00-20	16	1038	259	7.0	2900	880	TH702C
10.00-20	18	1073	278	7.5	3350	910	TH702C
11.00-20	18	1105	293	8.0	3650	910	TH702C



**TH702C**

# ATV Tyre

# ALL TERRAIN VEHICLE TYRE



**TH100**

SIZE	PR	RIM	Load Capacity(kg)		Inflated Pressure(Kpa)		Pattern
			LBS	KG	PSI	KPA	
AT25X8-12 TL	6	6.5AT	340	155	7	45	TH100
AT25X10-12 TL	6	8.0AT	420	190	7	45	TH100
AT26X9-12 TL	6	7.0AT	410	185	7	45	TH100
AT26X11-12 TL	6	9.0AT	480	218	7	45	TH100

